602912-00 Page 1 of 4

MOBIL OIL CORPORATION MATERIAL SAFETY DATA BULLETIN

REVISED: 12/30/92

作者有效未来的大大的作品的作品的作品的作品的 I. PRODUCT IDENTIFICATION 单类解析的并充实的作品的作品的未由主义

MOBIL SHC 634

SUPPLIER:

24-HOUR EMERGENCY (CALL COLLECT):

(609) 737-4411

MOBIL OIL CORP. CHEMICAL NAMES AND SYNONYMS:

CHEMTREC:

SYN. HYDROCARBONS AND ADDITIVES

(800) 424-9300

USE OR DESCRIPTION:

PRODUCT AND MSDS INFORMATION:

GEAR AND BEARING LUBRICANT

(800) 662-4525

********** II. TYPICAL CHEMICAL AND PHYSICAL PROPERTIES *********

APPEARANCE: Straw Liquid

ODOR: Mild

VISCOSITY AT 40 C, CS: > 414.0 VISCOSITY AT 100 C, CS: 46.0

FLASH POINT F(C): > 410(210) (ASTM D-92)

POUR POINT F(C): -40(-40)

MELTING POINT F(C): NA BOILING POINT F(C): > 600(316)

VOC: < 5.00(Wt. %); 0.354 lbs/gal

RELATIVE DENSITY, 15/4 C: 0.849

SOLUBILITY IN WATER: Negligible

VAPOR PRESSURE-mm Hg 20C: < .1

NA=Not Applicable NE=Not Established D=Decomposes FOR FURTHER INFORMATION, CONTACT YOUR LOCAL MARKETING OFFICE.

*********** III. POTENTIALLY HAZARDOUS INGREDIENTS ************

None

SEE SECTIONS XII AND XIII FOR REGULATORY AND FURTHER COMPOSITIONAL DATA.

--- INCLUDES AGGRAVATED MEDICAL CONDITIONS, IF ESTABLISHED ---THRESHOLD LIMIT VALUE: 5.00 mg/m3 Suggested for Oil Mist EFFECTS OF OVEREXPOSURE: Not expected to be a problem.

********** V. EMERGENCY AND FIRST AID PROCEDURES *********** --- FOR PRIMARY ROUTES OF ENTRY ---

EYE CONTACT: Flush thoroughly with water. If irritation persists, call a physician.

SKIN DNTACT: Wash contact areas with soap and water.

INHALATION: Remove from further exposure. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance and call a physician. If breathing has stopped, use mouth to mouth resuscitation.

INGESTION: Not expected to be a problem when ingested. If uncomfortable seek medical assistance.

AGC2G000048

ITIVNII

```
*********************

VI. FIRE AND EXPLOSION HAZARD DATA **********

FLASH POINT F(C): > 410(210) (ASTM D-92)

FLAMMABLE LIMITS. LEL: .67 UEL: 7.07

EXTINGUISHING MEDIA: Carbon dioxide, foam, dry chemical and water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Water or foam may cause frothing.

Use water to keep fire exposed containers cool. Water spray may be used to flush spills away from exposure. For fires in enclosed areas, firefighters must use self-contained breathing apparatus.

Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None.
```

NFPA HAZARD ID: Health: 0, Flammability: 1, Reactivity: 0

ENVIRONMENTAL IMPACT: Report spills as required to appropriate authorities. U. S. Coast Guard regulations require immediate reporting of spills that could reach any waterway including intermittent dry creeks. Report spill to Coast Guard toll free number (800) 424-8802. In case of accident or road spill notify CHEMTREC (800) 424-9300.

PROCEDURES IF MATERIAL IS RELEASED OR SPILLED: Adsorb on fire retardant treated sawdust, diatomaceous earth, etc. Shovel up and dispose of at an appropriate waste disposal facility in accordance with current applicable laws and regulations, and product characteristics at time of disposal.

WASTE MANAGEMENT: Product is suitable for burning in an enclosed, controlled burner for fuel value or disposal by supervised incineration. Such burning may be limited pursuant to the Resource Conservation and Recovery Act. In addition, the product is suitable for processing by an approved recycling facility or can be disposed of at any government approved waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

************** IX. SPECIAL PROTECTION INFORMATION ***********************
EYE PROTECTION: Normal industrial eye protection practices should be employed.

SKIN PROTECTION: No special equipment required. However, good personal hygiene practices should always be followed.

RESPIRATORY PROTECTION: No special requirements under ordinary conditions of use and with adequate ventilation.

VENTILATION: Use in well ventilated area.

MOBIL SHC 634

---ACUTE TOXICOLOGY---

ORAL TOXICITY (RATS): Nontoxic --- Based on testing of similar products and/or the components.

DERMAL TOXICITY (RABBITS): Nontoxic --- Based on testing of similar products and/or the components.

INHALATION TOXICITY (RATS): Not established

EYE IRRITATION (RABBITS): Expected to be non-irritating. --- Based on testing of similar products and/or the components.

SKIN IRRITATION (RABBITS): Expected to be non-irritating. ---Based on testing of similar products and/or the components.

Transport Information:

DOT:

Shipping Name: Not applicable Hazard Class: Not applicable

US OSHA HAZARD COMMUNICATION STANDARD: Product assessed in accordance with OSHA 29 CFR 1910.1200 and determined not to be hazardous.

RCRA INFORMATION: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity, or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

U.S. Superfund Amendments and Reauthorization Act (SARA) Title III: This product Contains no "EXTREMELY HAZARDOUS SUBSTANCES".

SARA (311/312 - FORMERLY 302) REPORTABLE HAZARD CATEGORIES: None

This product contains no chemicals reportable under SARA (313) toxic release program.

THE FOLLOWING PRODUCT INGREDIENTS ARE CITED ON THE LISTS BELOW:

CHEMICAL NAME

CAS NUMBER
LIST CITATIONS

*** NO REPORTABLE INGREDIENTS ***

--- REGULATORY LISTS SEARCHED ---

```
1 = ACGIH ALL
                6 = IARC 1
                             11 = TSCA 4 17 = CA P65
                                                          22 - MI 293
2 = ACGIH A1
                7 - IARC 2A
                              12 = TSCA 5a2 18 = CA RTK
                                                          23 - MN RTK
3 = ACGIH A2
                8 = IARC 2B
                              13 = TSCA 5e 19 = FL RTK
                                                          24 - NJ RTK
4 - NTP CARC
                9 = OSHA CARC 14 = TSCA 6
                                            20 - IL RTK
                                                          25 ≈ PA RTK
5 = NTP SUS
               10 = OSHA Z
                              15 = TSCA 12b 21 = LA RTK
                                                          26 = RI RTK
                              16 = WHMIS
```

CARC - CARCINOGEN; SUS - SUSPECTED CARCINOGEN

NOTE: MOBIL PRODUCTS ARE NOT FORMULATED TO CONTAIN PCBS.

3225 GALLOWS ROAD, FAIRFAX, VA 22037

(800) 227-0707 X3265

INGREDIENT DESCRIPTION PERCENT CAS NUMBER |<-->| |<---->| > 95.00 CONTAINS THE FOLLOWING BASE OILS: 68037-01-4 1-DECENE, HOMOPOLYMER, HYDROGENATED 16958-92-2 HEXANEDIOIC ACID, DITRIDECYL ESTER FOR MOBIL USE ONLY: MHC: 0* 0* NE 0* 0*, MPPEC: A, PPEC: , US92-785 APPROVE CCODE:10 11/13/92 REQ: US - MARKETING INFORMATION GIVEN HEREIN IS OFFERED IN GOOD FAITH AS ACCURATE, BUT WITHOUT GUARANTEE. CONDITIONS OF USE AND SUITABILITY OF THE PRODUCT FOR PARTICULAR USES ARE BEYOND OUR CONTROL: ALL RISKS OF USE OF THE PRODUCT ARE THEREFORE ASSUMED BY THE USER AND WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE IN RESPECT TO THE USE OR SUITABILITY OF THE PRODUCT. NOTHING IS INTENDED AS A RECOMMENDATION FOR USES WHICH INFRINGE VALID PATENTS OR AS EXTENDING LICENSE UNDER VALID PATENTS. APPROPRIATE WARNINGS AND SAFE HANDLING PROCEDURES SHOULD BE PROVIDED TO HANDLERS AND USERS. PREPARED BY: MOBIL OIL CORPORATION ENVIRONMENTAL HEALTH AND SAFETY DEPARTMENT, PRINCETON, NJ FOR FURTHER INFORMATION, CONTACT: MOBIL OIL CORPORATION, PRODUCT FORMULATION AND QUALITY CONTROL